
BELDEN
SENDING ALL THE RIGHT SIGNALS


- For Residential or Commercial use.

ORDER CODE	DESCRIPTION	PRICE/1000FT
BN-1189A-WH	RG-6 Quad Shield Broadband Coaxial Cable, White color, 1000 feet	
BN-1189A-BK	RG-6 Quad Shield Broadband Coaxial Cable, Black color, 1000 feet	
BN-9116-BK	RG-6 Duobond Shield Broadband Coaxial Cable, Black color, 1000 feet	
BN-543945	New Generation RG-59 Security Coaxial Cable, CCTV Usage, 1000 feet	
BN-549945	New Generation RG-59 Security Composite Cable, CCTV Plus Audio Applications, 1000 feet	
BN-5300UG	New Generation Security and Alarm Cable, Residential, Light Commercial Applications, 1000 feet	
BN-5339B5	New Generation RG-6 Duofoil Shield Security Coaxial Cable, CCTV and MATV Usage, 1000 feet	
BN-5339Q5	New Generation RG-6 Quad Shield Security Coaxial Cable, CCTV Usage, 1000 feet	
BN-5500UE	New Generation Security and Alarm Cable, Commercial Applications, 2 conductors, 1000 feet	
BN-5502UE	New Generation Security and Alarm Cable, Commercial Applications, 4 conductors, 1000 feet	

**PLEASE
CALL
FOR
PRICE**


BELDEN 3GHz HIGH FLEXIBLE VIDEO PATCH CABLES

- Cable : Belden 1505F RG59/RG6 broadband coax.
- Hi-Flex cable construction replaces traditional stiff and rigid video cables.
- Stranded center conductor and 94% tinned braid shielded structure - very flexible for video patching application at home, or broadcasting industry.
- Injection molded strain relief on connectorized ends.
- High performance rating, up to 3 GHz stability.
- Corrosion-resistant 24K gold plated center pin.
- Available in 6 colors.

BELDEN
SENDING ALL THE RIGHT SIGNALS


PATCH CABLES WITH BNC CONNECTORS

- Connectors : BNC male connectors.



ORDER CODE	DESCRIPTION	1-49	50-99	100+
H50-BB-11-TT-01-XX	BNC Male to BNC Male cable, 1 foot	\$6.07	5.80	5.38
H50-BB-11-TT-03-XX	BNC Male to BNC Male cable, 3 feet	7.66	7.31	6.79
H50-BB-11-TT-06-XX	BNC Male to BNC Male cable, 6 feet	10.03	9.58	8.89
H50-BB-11-TT-10-XX	BNC Male to BNC Male cable, 10 feet	13.20	12.60	11.70

- Custom Length: \$5.50 + \$0.80/ft.

XX = Color WH BK BL GN RD YL

PATCH CABLES WITH F CONNECTORS

- Connectors : 3 styles of F connectors -
 - 180° Threaded Type, easy snap-in
 - Push-On Type, and 90° Threaded Type.



H50-FF-99-TT

ORDER CODE	DESCRIPTION	1-49	50-99	100+
H50-FF-11-TT-01-XX	Threaded 180° Male to 180° Male, 1 foot	\$6.07	5.80	5.38
H50-FF-11-TT-03-XX	Threaded 180° Male to 180° Male, 3 feet	7.66	7.31	6.79
H50-FF-11-TT-06-XX	Threaded 180° Male to 180° Male, 6 feet	10.03	9.58	8.89
H50-FF-11-TT-10-XX	Threaded 180° Male to 180° Male, 10 feet	13.20	12.60	11.70
H50-FF-11-PP-01-XX	Push-On 180° Male to 180° Male, 1 foot	6.07	5.80	5.38
H50-FF-11-PP-03-XX	Push-On 180° Male to 180° Male, 3 feet	7.66	7.31	6.79
H50-FF-11-PP-06-XX	Push-On 180° Male to 180° Male, 6 feet	10.03	9.58	8.89
H50-FF-11-PP-10-XX	Push-On 180° Male to 180° Male, 10 feet	13.20	12.60	11.70
H50-FF-99-TT-01-XX	Threaded 90° Male to 90° Male, 1 foot	6.07	5.80	5.38
H50-FF-99-TT-03-XX	Threaded 90° Male to 90° Male, 3 feet	7.66	7.31	6.79
H50-FF-99-TT-06-XX	Threaded 90° Male to 90° Male, 6 feet	10.03	9.58	8.89
H50-FF-99-TT-10-XX	Threaded 90° Male to 90° Male, 10 feet	13.20	12.60	11.70

- Custom Length: \$5.50 + \$0.80/ft.

XX = Color WH BK BL GN RD YL

PREMIUM RG-59 75 OHM COAX CABLES

BNC MALE TO BNC MALE, GOLD CONNECTOR

- Cable: RG-59 B/U.
- Conductor: 1/0.58 Bare Copper + PE Insulation + Braid (16*7/0.12), PVC Jacket.
- Connectors: BNC Male, gold flash contact.
- Insulator: 75 Ohm white gold plated shell.
- Assembly Boot: 45P PVC black, molded.



ORDER CODE	LENGTH	1-49	50-99	100+
C33-BNC-MM-03	3 feet	\$4.93	4.70	4.37
C33-BNC-MM-06	6 feet	5.63	5.38	4.99
C33-BNC-MM-10	10 feet	6.69	6.38	5.93
C33-BNC-MM-15	15 feet	8.71	8.32	7.72
C33-BNC-MM-25	25 feet	10.74	10.25	9.52

- Custom Length: Please Call for Price.

F CONNECTOR MALE TO F CONNECTOR MALE (PUSH-ON TYPE)

- Cable: RG-59 B/U.
- Conductor: 1/0.58 Bare Copper + PE Insulation + Braid (16*7/0.12), PVC Jacket.
- Connectors: F Connectors Male, gold flash contact.
- Insulator: White gold plated shell (180° RG59U Push-On Type).
- Assembly Boot: 45P PVC black, molded.



- Custom Length: Please Call for Price.

F CONNECTOR MALE TO F CONNECTOR MALE (SCREWED TYPE)

- Cable: RG-59 B/U.
- Conductor: 1/0.58 Bare Copper + PE Insulation + Braid (16*7/0.12), PVC Jacket.
- Connectors: F Connectors Male, gold flash contact.
- Insulator: White gold plated shell (180° RG59U Screwed Type).
- Assembly Boot: 45P PVC black, molded.



- Custom Length: Please Call for Price.